




QUICKEST QUILT

1. Cut all fabric, for top, lining and batt, into equal width strips. Suggested widths from 4" to 6". Do not cut the lengths until needed.
2. Begin at the center of the quilt. Cut 3 strips of quilt top fabric and 3 strips of lining, and 3 strips of batt to equal lengths. (My sample quilt uses $5\frac{1}{2}$ " x 24" length.)
3. Use 2 lining and 2 top strips and 1 batt strip. Stack these as follows: batt on bottom, then 2 lining strips with right sides fabric together. Then add 2 top strips that are right sides fabric together. Sew through all five layers along one long side using $\frac{1}{4}$ " seam.
4. Open fabric right side out. You have two "logs" connected with the seam enclosed. One "log" is stuffed. Place batt between the layers of fabric in the other log (this is the true center of the quilt). Pin the batt in place.
5. Add remaining strip of lining right side of fabric to the lining side. Place remaining strip of top right sides of fabric together on the top side of the center log. Place the last piece of batt under all layers. Sew with $\frac{1}{4}$ " seam along the long side.
6. Open fabric strips right side out. Three logs are connected. All are stuffed. All seams enclosed.
7. Cut 2 strips top fabric and 2 strips lining and 2 strips batt the length required across the top of the three beginning logs. That is 1 of each for the top and bottom ends of the beginning logs. The diagram shows beginning logs #1, 2, 3. This step adds strips numbered 4. Place and sew these as before.
8. Cut 2 each of top, lining and batt to measure for each long side (#5 in diagram). Sew in the same manner for a fully enclosed, already stuffed, finished on top and on lining sides.



measure for #4

Continue adding to top and bottom (#6, 8, etc.) and to sides (#5, 7, etc.) until the quilt is desired width. If width is reached before length is satisfied, continue adding logs to top and bottom but no more to the sides.

IT IS READY TO BIND!

